



## Typical Inspection Data:

Density @ 20°C	1.068 g/cm <sup>3</sup>
Viscosity @ -40°C	850 cSt
Viscosity @ 100°C	2.2 cSt
Colour	Colourless to amber
Equilibrium Reflux Boiling Point	278°C
Wet Equilibrium Reflux Boiling Point	183°C
pH (50% EtOH)	7.3

## DOT 5.1

### Synthetic Brake Fluid

**Recommended by Comma for applications requiring:**

FMVSS 116 DOT 5.1, ISO 4925 (Classes 3, 4 & 5.1)

#### Product Features:

- The highest quality brake fluid specially formulated for use in today's high performance vehicles. Minimum wet boiling point of 180°C - ideal for all ABS systems.
- Non-Silicone based can be mixed safely with DOT 3 & DOT 4 Fluids.

#### Directions for use:

- **IMPORTANT** - Follow vehicle manufacturer's recommendations.
- Keep Brake Fluid clean and dry.
- Store in original container only.
- Keep container clean and tightly closed to prevent water absorption.
- Caution: Do not refill container and do not use for other liquids.
- Take care not to spill on paintwork. If spilt wash off with plenty of water. Do not rub.
- All brake fluids absorb moisture and therefore they must be checked or changed regularly.

#### Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

#### Shelf Life:

- 3 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 02-03-2021