



## Typical Inspection Data:

Density @ 20°C	1.124 g/cm <sup>3</sup>
Appearance	Clear violet liquid
Boiling point	177°C
Reserve Alkalinity	10ml
Water Content	2.6%
Refractive Index	1.434
Appearance	Clear violet liquid
Boiling point	Min 170°C

## Protection Levels:

Xstream® G40® (%)	Approx. Protection (°C)
33	-18
50	-36
60	-52

## Xstream® G40® Antifreeze & Coolant Concentrate

### Glysantin® G40® by BASF is approved by:

Audi (vehicles built as from 08/2007, TL 774-G), Bentley (vehicles built as from 2008, TL 774-G), Claas, Cummins (CES 14603), Deutz (DQC CC-14), Ducati (TL 774-G), Irizar, Lamborghini (vehicles built as from 2009, TL 774-G), Liebherr (vehicles built as from 2015, Minimum LH-01-COL3A), MAN Energy Solutions (MAN engine type MAN 175D, BASF-CW-GLY00G40-01), MAN Truck & Bus (vehicles built as from 12/2012, MAN 324 Typ Si-OAT), Mercedes-Benz Cars (vehicles built as from 05/2014, MB-Approval 325.6), Mercedes-Benz Truck & Bus (vehicles built as from 10/2011, MB-Approval 325.5), MTU (selected engines, MTL 5048), Porsche (vehicles built as from 2010, TL 774-G), SEAT (vehicles built as from 2008, TL 774-G), SETRA (MB-Approval 325.5), Skoda (vehicles built as from 09/2008, TL 774-G), Volkswagen (vehicles built as from 09/2008, TL 774-G).

This Engine Coolant Concentrate conforms to the requirements of: BS 6580:2010

### Product Features:

- Ethylene glycol based antifreeze with Si-OAT (Silicated Organic Additive Technology) inhibitors.
- Protects against corrosion, overheating and freezing.
- Typical service life of up to 5 years.
- Safeguarded with bittering agent to help prevent accidental ingestion.
- To ensure correct antifreeze & coolant selection check Comma's latest application guide in store or online at [www.CommaOil.com](http://www.CommaOil.com).

### Directions for use:

1. Dilute with de-ionised water in accordance with the vehicle manufacturer's instructions.
2. Pour into vehicle cooling system.
3. Do not mix different types of Antifreezes. If in doubt about product suitability, refer to vehicle handbook.
4. Remove spills from paintwork immediately.

### Handling:

- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried.
- Wash off any spillage on paintwork immediately.
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 01-09-2022